

NLS-HR15

Hand-held Barcode Scanner

(NLS-HR1550-3E)

Support PDF417 & MicroPDF417



ZigBee

The NLS-HR1550-3E hand-held barcode scanner (cordless) is able to read 1D symbologies as well as PDF417 and MicroPDF417. This model adopts Zigbee technology to realize wireless communication and supports standard RS-232 / USB. With good performance, this rugged scanner is very suitable for applications in supermarkets, shopping malls and warehouse environment application, etc.

Product Features

- **Data Acquisition**
Support common 1D barcodes and PDF417 and MicroPDF417 stacked 2D barcode.
- **Operating Modes**
Data Transmission supports Synchronous, Asynchronous and Batch mode. Memory capacity for offline scanning is up to 4095 EAN-13 barcodes of 13mil.
- **Zigbee Wireless**
Zigbee technology, supporting long-distance communication up to 50m & easy networking to expand coverage
- **Super One Pair**
Cradle and scanner(s) can be paired one-to-one or one-to-many simply via the Match key on cradle. And the cradle is also able to seek the paired scanner(s) via the Match key.

Specifications

Performance	
Light Source	620nm Visible Red LED
Image Sensor	Linear imager
Symbologies	Code128, EAN-13, EAN-8, Code39,UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN, Code 93, UCC/EAN-128, GS1 Databar, PDF417(max. 255 bytes), MicroPDF417(max. 255 bytes), etc.
Resolution	≥ 4mil
Scan Angle**	Pitch ±55°@ 0°Roll and 0°Skew
	Roll ±30°@ 0°Pitch and 0°Skew
	Skew ±75°@ 0°Roll and 0°Pitch
Minimum Symbol Contrast	15%
Scan Rate	350 scans per second
Interface	RS-232, USB
Mechanical	
Dimensions of Scanner(L x W x H)	113.5 x 73 x 159 mm
Dimensions of Cradle(L x W x H)	195 x 82.5 x 47 mm
Weight of Cordless Scanner	210 g (Including battery)
Weight of Cradle	150 g
Notification	Beep and LED indicator
Power Adaptor	Output: DC5V, 1.5A Input: AC100~240V, 50~60Hz
Environmental	
Operating Temperature	-10°C to 50°C (14°F to 122°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Humidity	5% ~ 95% (Non-condensing)
Static Discharge	±12KV (Air discharge), ±8KV (Contact discharge)
Sealing	IP52
Wireless	
Operating Modes	Synchronous, Asynchronous and Batch modes
Radio Technology	2.4 to 2.4835 GHz ISM Band, Zigbee technology
Communication Distance	≥ 50 m
Data Rate	20-250 KBps
Battery	2200mAh Li-ion Battery
Expected Hours of Operation	>17 hours
Charging Time	Around 3.5 hours for full charge
Number of Scans	60,000 scans per charge
Certifications	

FCC Part15 Class B, CE EMC Class B

****Test conditions:**

Code 39, 3 Bytes; Resolution=10mil; W:N=2.5:1; PCS=0.8; Barcode Height=40mm; Scan Distance=210mm, T=23 , Illumination= 200 LUX

Contact Us

Newland China

+86-400-608-0591

marketing@nlscan.com

Newland Europe

+31(0)-345-87-0033

info@newland-id.com

Newland Taiwan

+886-2-7731-5388

info@newland-id.com.tw

Newland North America

+1-510-490-3888

info@newlandna.com

www.nlscan.com

